

RR KABEL LIMITED													
RRKL/CU-ARM-UAR/LP/07/25						w.e.f. 1st July, 2025							
PRICE LIST													
POWER CABLES (COPPER ARMoured / UNARMoured)													
RR KABEL make Power/Control Cables, Solid Copper Conductor upto 6.0 Sq.mm balance Stranded, XLPE Insulated, cores laid up, PVC tape inner sheathed for Multicore Cables, Unarmoured / Armour (1. Single core cables - Aluminium wire upto 70.0 sq.mm balance Aluminum strip, 2. Glavanised wire for cables upto 10Cx1.5 sq.mm, 8Cx2.5 sq.mm, 2Cx10.0 sq.mm, 3Cx10.0 Sq.mm, 4Cx6.0 Sq.mm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/ 1100 V grade as per IS 7098 (Part 1) 1988. (HSN CODE : 8544)													
Rate Per Meter (INR)													
(UNARMoured CABLES) (2XY)						(ARMoured CABLES) (2XWY / 2XFY)							
No. of Cores	1.5	2.5	No. of Cores	1.5	2.5	No. of Cores	1.5	2.5	No. of Cores	1.5	2.5		
2	179	271	14	880	1590	2	229	324	14	1063	1670		
3	253	378	16	1054	1822	3	292	418	16	1188	1897		
4	324	510	19	1261	2155	4	360	540	19	1409	2234		
5	395	638	24	1597	2721	5	438	663	24	1763	2796		
6	475	757	27	1764	3022	6	521	780	27	1960	3136		
7	538	863	30	2094	3583	7	574	880	30	2186	3772		
8	655	978	37	2712	4296	8	734	1074	37	2836	4406		
10	782	1121	44	3172	5122	10	835	1236	44	3313	5145		
12	835	1372	61	4641	7049	12	928	1436	61	4876	7460		
Size (Sq.mm)	(UNARMoured CABLES) (2XY)					(ARMoured CABLES) (2XWY/2XFY) (2XWY / 2XFY)							
	1 Core	2 Core	3 Core	3.5 Core	4 Core	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core	6 Core	7 Core
4.0	-	384	546	-	675	-	450	603	-	773	1133	1427	1573
6.0	-	560	806	-	993	-	634	870	-	1137	1647	2013	2309
10.0	-	971	1367	-	1629	-	1007	1415	-	1848	2505		
16.0	719	1368	1986	-	2550	860	1494	2070	-	2734	3594	-	-
25.0	1155	2279	3168	3774	4148	1272	2454	3350	4015	4416	6407	-	-
35.0	1597	3157	4414	5082	5944	1728	3363	4718	5389	6265	8675	-	-
50.0	2187	4329	6001	7187	7946	2335	4392	6378	7507	8500	11879	-	-
70.0	3114	6173	8839	10368	11740	3280	6524	9313	10780	12270	18687	-	-
95.0	4245	8438	12646	14718	16464	4359	9015	12913	14787	17044	-	-	-
120.0	5351	10664	14804	18821	21079	5485	10750	15834	19447	21237	-	-	-
150.0	6687	13300	19824	22898	26348	6823	13459	20137	23525	26976	-	-	-
185.0	8207	16066	24466	28606	32621	8389	16660	25596	29948	34190	-	-	-
240.0	10602	20570	31975	37353	43225	10778	21463	33249	38656	44106	-	-	-
300.0	13225	25631	39657	46053	53379	13438	27185	41906	48463	56084	-	-	-
400.0	17377	34210	49435	56307	70228	17566	36980	53824	61252	74979	-	-	-
500.0	21957	-	-	-	-	22207	-	-	-	-	-	-	-
630.0	27603	-	-	-	-	27979	-	-	-	-	-	-	-
800.0	35130	-	-	-	-	35507	-	-	-	-	-	-	-
1000.0	43914	-	-	-	-	44289	-	-	-	-	-	-	-
Additional to be charged for Special Construction													
A) Tinning	3%	G) HR PVC Insulation		10%	As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the Price List are only for guidelines and as per market convention, it may vary within the prescribed limit of IS:8130-1994, with related classes and tables.								
B) Stranding (upto 6.0 Sq.mm)	4%	H) HR PVC Inner Sheath		7.5%									
C) Extruded Inner Sheath	4.0%	I) HR PVC Outer Sheath		7.5%									
D) Round Wire Armouring:		J) FR-LSH Outer Sheath (Power Cables)											
1. 1C x 95.0 Sq.mm & above	9.0%	Upto 6.0 Sq.mm		11.5%									
2. 12C x 1.5 Sq.mm & above	18%	10.0 Sq.mm & above		6%									
3. 9C x 2.5 Sq.mm & above	18%	K) FR-LSH / LSZH Loading - Control Cables (Inner / Outer Sheath)											
4. 4C x 10.0 Sq.mm & above	18%												
5. 2C x 16.0 & above	18%	Cores	FR-LSH		LSZH		* MOQ will be applicable for all Special Items						
6. 3C x 16.0 & above	18%		Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath							
E) Oxygen Index (FR)	4.0%	2C to 4C		7.5%	9%	22.5%	22.5%	* The above material will be supplied from our Waghodia Unit.					
F) PVC Insulation (as per IS 1554)	7.5%	5C to 10C		7.5%	6%	22.5%	22.5%						
Terms & Conditions:													
> The above rates are exclusive of GST & any other statutory levies which shall be charged extra.													
> Freight will be Extra as applicable													
Note: This is revised Price List, hence our all previous Price Lists, Discount Policies are hereby ceased to exist.													
THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE													

RR KABEL LIMITED
RRKL/AL-ARM-UAR/LP/07/25
w.e.f. 1st July, 2025
PRICE LIST
POWER CABLES (AL. ARMoured / UNARMoured)

RR KABEL make Power Cables, Solid Aluminum conductor upto 10.0 sq.mm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape inner sheathed for Multicore Cables, Unarmoured / Armour (1. Single core Cables - Aluminium wire upto 70.0 sq.mm balance Aluminum strip, 2. Galvanised wire for cables upto 2Cx10.0 sq.mm, 3Cx10.0 sq.mm, 4Cx6.0 sq.mm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/ 1100 V grade as per IS 7098 (Part 1) 1988. (HSN Code : 8544)

Size (in Sq.mm)	CORES / RATE PER METER (INR)									
	(UNARMoured CABLES) (A2XY)					(ARMoured CABLES) (A2XW _a Y/ A2XF _a Y) (A2XWY / A2XFY)				
	1C	2C	3C	3.5C	4C	1C	2C	3C	3.5C	4C
4.0	-	122	152	-	182	-	217	233	-	271
6.0	-	170	201	-	245	-	263	287	-	343
10.0	-	245	274	-	322	-	333	371	-	472
16.0	119	249	309	-	409	214	379	399	-	504
25.0	172	322	453	574	604	282	405	531	617	660
35.0	222	422	599	649	720	341	504	675	750	855
50.0	285	530	738	879	963	420	653	878	1016	1142
70.0	393	763	1063	1201	1382	538	874	1204	1369	1552
95.0	505	905	1293	1536	1647	645	1080	1483	1717	1935
120.0	630	1128	1739	1975	2101	748	1289	1860	2151	2430
150.0	779	1403	2046	2310	2601	891	1585	2284	2549	2988
185.0	964	1673	2578	2955	3220	1095	1905	2827	3227	3675
240.0	1223	2188	3327	3617	4207	1353	2526	3610	4053	4746
300.0	1512	2674	4079	4687	5124	1665	3096	4461	4986	5850
400.0	1946	3337	5089	5856	6549	2103	4020	5702	6369	7302
500.0	2446	4257	7203	8081	9134	2620	5428	7645	9003	10095
630.0	3030	5419	9036	10721	12223	3233	6677	9718	11032	13252
800.0	3781	-	-	-	-	3974	-	-	-	-
1000.0	4767	-	-	-	-	4887	-	-	-	-

Additional to be charged for Special Construction

A) Stranding (upto 10.0 Sq.mm)	10%	H) FR-LSH / LSZH Loading - (Inner / Outer Sheath) :						
B) Round Wire Armouring		Size	FR-LSH		LSZH			
			Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		1. 1C x 95.0 & above	30%	Upto 1C x 16.0	NA	15%	NA	37.50%
		2. 2C x 16.0 & above	30%	1C x 25.0 to 1C x 50.0	NA	15%	NA	30%
		3. 3C x 16.0 & above	30%	1C x 70.0 & above	NA	11.50%	NA	26.0%
		4. 3.5C x 25.0 & above	30%	Multicore upto 16.0	15%	11.5%	22.5%	30%
5. 4C x 10.0 & above	30%							
C) Oxygen Index (FR)	4.0%	Multicore 25.0 to 50.0	11.5%	11.5%	18.0%	22.5%		
D) PVC Insulation (as per IS 1554)	12%	Multicore 70.0 & above	7.5%	7.5%	22.5%	18%		
E) HR PVC Insulation	15%	I) Extruded PVC Inner Sheath :			* MOQ will be applicable for all Special Items			
F) HR PVC Inner Sheath	7.50%	1. Upto 50.0 Sq.mm.	5%					
G) HR PVC Outer Sheath	7.50%	2. 70.0 Sq.mm. & above	2.5%					

Terms & Conditions:

> The above rates are exclusive of GST & any other statutory levies which shall be charged extra.

> Freight will be Extra as applicable

Note: This is revised Price List, hence our all previous Price Lists, Discount Policies are hereby ceased to exist.

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE